



# EPIC-E41\_J126L VER:1.0E

[ Celeron\_J4125 ]



<b>Model No.</b>	<b>EPIC-E41_J126L VER:1.0E</b>
<b>Processor</b>	Integrated Intel®Celeron J4125 2.0GHz Quad core Quad thread processor ,TDP 10W Compatible with Intel® Gemini Lake all series CPU
<b>Chipset</b>	SOC
<b>Memory</b>	1* SODIMM slot ,supports single channel 2400MHz DDR4 memory, is up to 8GB
<b>Display</b>	Intel® UHD Graphics 600 1* VGA,1*HDMI,1* LVDS
<b>Ethernet</b>	2* RTL8111H Gigabit Ethernet,supports Wake on LAN/PXE function
<b>Storage</b>	1* 7pin SATA3.0, the transfer rate is up to 3Gbps 1* MSATA slot, supports Intel protocol SSD solid state drive, transmission rate reaches 6Gbps
<b>Audio</b>	Onboard ALC662 6-channel high-fidelity audio controller, supports MIC/Line-out. Amplifier It is recommended to use 4 Ω 3W horn for power amplifier
<b>Expansion Slot</b>	1* Mini-PCIE slot, supports WIF/4G module
<b>Backplane I / O interface</b>	1* DC 12V Power input interface 1* VGA 1* HDMI 2* USB3.0,1* USB2.0 2* RJ45 Gigabit Network Interface 1* Line-out(green)
<b>Built in I / O interface</b>	1* DC power interface, 1*4pin supports 12V Power input and output 1* JVGA, 1*12pin, Same signal as DB15 1* LVDS,2*15pin,supports dual channels 24BIT 1* Screen backlight power supply interface 1*6pin 4* USB2.0,2*5pin 6* RS232 serial ports ,COM2/COM3 supports RS485/422 1*Hard disk power supply interface 1*4pin 1* Front audio interface 2*5pin 1*Power amplifier interface, 1*4pin 1* SIM card slot

	1*Front panel function button and indicator light interface, 2*5pin
<b>Fan interface</b>	Fanless cooling ,reserve 1 * 4Pin CPU intelligent fan interface and 1 * 4Pin system fan interface
<b>GPIO</b>	Support 4-way input and output GPIO
<b>BIOS</b>	64Mb Flash ROM
<b>Watchdog</b>	Support hardware reset function (256 levels, 0 ~ 255 seconds)
<b>OS</b>	Windows 10/Linux
<b>Power Type</b>	DC 12V
<b>working temperature</b>	-10℃~60℃
<b>Storage temperature</b>	-20℃~70℃
<b>Working humidity</b>	5%-95%(Relative humidity, non condensing)
<b>Dimension</b>	148mm x 102mm

## Order information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485/422	Power
1	EPIC-E41_J126L VER:1.0E	J4125	2.0G	1* SODDR4	1	1	2ch*24BIT	/	2*8111H	7	6	COM2/3	DC12V