

# EPIC-E73\_I526L VER: 1.1

(i5-6200U)



<b>Model No.</b>	EPIC-E73_I526L VER:1.1 (6200U)
<b>Processor</b>	Integrated Intel® I5-6200U 2.3GHz Dual core Quad thread processor , TDP15W
	Compatible with Intel® Skylake-U Celeron/PentiumI3/I5/I7 28W low power consumption processors
<b>Chipset</b>	SOC
<b>Memory</b>	1*SODIMM slot,support DDR4 2133MHz memory, up to 32GB
<b>Display</b>	Integrated Intel® HD Graphics 520,supports DirectX 12 OpenGL 4.5, supports 4K
	1*VGA,1* HDMI,1*LVDS , supports dual channels 24Bit
<b>Ethernet</b>	2* Intel WGI211AT Gigabit Ethernet,supports Wake on LAN/PXE function
<b>Storage</b>	1* 7pin SATA3.0, the transfer rate is up to 6Gbps
	1* MSATA slot, supports Intel protocol SSD,the transfer rate is up to 6Gbps
<b>Audio</b>	Onboard USB Audio HS-100B sound card , supports 6 vocal channels high fidelity audio controller,supports Line-out, power amplifier
	Support power amplifier 3D /3W dual channels
<b>Expansion Slot</b>	1* Mini-PCIE slot,supports WIFI/4G module
<b>Rear I/O interface</b>	1* DC_Jack 12V power input interface
	1* HDMI
	1* VGA
	2* USB3.0
	1* USB2.0
	2* RJ45 Gigabit Network Interface
	1* Line-out (Green)
<b>Built in I / O interface</b>	1* 4pin DC power interface,supports 12V power input output
	1* JVGA, 1*12pin (Same signal as DB15)
	1* LVDS, supports Dual channel 24BIT,share row pin with EDP,can choose to do EDP
	1* Backlight power supply interface,1*6pin
	6* RS232 COM ( COM1 supports the 9 <sup>th</sup> pin charged ,COM2 supports RS485 function)
	4* USB2.0, 2*5pin
	1*Front audio interface, 2*5pin
	1*Power amplifier interface,1*4pin
	1*Hard disk power supply interface, 1*4pin
	1*Front panel function button and indicator light interface, 2*5pin

<b>Fan Connector</b>	1*4pin CPU smart fan connector, 1*3pin system fan connector
<b>GPIO</b>	Support 4-way input output GPIO function
<b>BIOS</b>	64Mb Flash ROM
<b>Watchdog</b>	Support hardware reset function (L256, 0~255 seconds)
<b>OS</b>	Windows7/Windows 10/Linux
<b>Power Type</b>	DC 12V
<b>Working temp.</b>	-10℃~60℃
<b>Storage temp.</b>	-20℃~70℃
<b>Working Humidity</b>	5%-95% ( relative humidity, non-condensing)
<b>Dimension</b>	148mm x 102mm

## Order information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485	Power
1	EPIC-E73_I526L VER:1.1(6200U)	I5-6200U	2.3G	1* SODDDR4	1	1	2ch*24bit	/	2*211AT	7	6	1	DC12V