

H570VM (VER: 1.0)

MICRO_ATX SOCKET LGA 1200 SERIES



Model No.	H570VM VER:1.0
Processor	Supports LGA1200 10th/11th Intel® Celeron/Pentium/Core™ i3/i5/i7/i9 processors
Chipset	Intel H570 High speed chipset
Memory	4*DDR4 DIMM, supports dual channels 3200MHz memory, up to 128GB
Display	Integrated Intel® HD Graphics, support DirectX12.1, OpenGL4.5 Provide:1*VGA & 2*HDMI1.4,
Ethernet	2* Intel I226V 2.5G Gigabit Ethernet ,supports Wake on LAN/PXE function
Storage	4* SATA3.0 ,the transfer rate is up to 6Gbps
	1* MSATA,supports Intel protocol SSD, the transfer rate is up to 6Gbps
	1* M.2 slot,supports M.2 2280 NVME PCIE x1/SATA
Audio	Onboard ALC897 7.1+2 high fidelity audio controller,supports Mic_in&Line_out/in
Expansion Slot	1* PCIE3.0 x16
	3* PCIE3.0 x4
	1* PCIE3.0 x1
	2* PCI
	1* M.2 slot, support M.2 Key_B 2242/2252 standard 4G/5G module
Rear I/O interface	1* PS/2 for K&M
	1* DB15 VGA
	1* HDMI1.4
	2* DB9 RS232 serial port, support RS485/422 function
	2* RJ45 Gigabit Ethernet port
	2* USB 2.0
	4* USB 3.0
	1* Line_out / 1* Line_in / 1* Mic_in
Inner I/O interface	1* PS/2 1*6pin
	1* JVGA 1*12pin
	1* JHDMI 2*8pin

	4* RS232 COM 2*5pin
	1* Front audio interface 2*5pin
	4* USB 2.0 2*5Pin
	2* USB3.0 2*10Pin
	1* TPM 2*6pin
	1* Front panel function button and indicator light interface 2*5pin
	1* LPT 2*13pin
	1* SIM slot
	1* 24pin ATX power input interface
	1* 8pin ATX power input interface
Fan Connector	1*4pin CPU smart fan connector,4* 4pin system smart fan connector
BIOS	128Mb Flash ROM
OS	Windows 10 /11 ; Linux
Watchdog	Support hardware reset function (L256, 0~255 seconds)
Power Type	ATX power input
Working temp.	0℃~60℃
Storage temp.	-20℃~70℃
Working Humidity	5%-95% (relative humidity, non-condensing)
Dimension	305mm x 245mm

ORDER INFORMATION:

No.	Model	Processor	Frequency	Southbridge	Memory	VGA	HDMI	DP	LAN	USB	COM	RS485/422	Power
1	H570VM VER:1.0	LGA1200	/	H570	4*DDR4	1	2	/	2*I226V	12	6	COM1/2	ATX