

TPC191-A210-3588A

Adopting ultra-thin bezel which is more suitable for embedded installation, aluminum alloy structure, fanless and fully enclosed design, up to IP65 dustproof and waterproof, widely used in industrial control, military, power, intelligent self-service terminal equipment and other automation applications. Widely used in industrial control, military, communication, electric power, intelligent self-service terminal equipment and other automation applications.

## Features


- 3mm Super Thin Front Bezel, Best for Embedded Cabinet.
  - Pure flat panel IP65 dust-proof and waterproof.
  - Self-developed ARM architecture industrial motherboard
  - RK3588 Octa-core with 6 TOPS NPU
  - Wide Temperature Adaptation Efficient Heat Dissipation.
  - Provide SDK package, Support secondary development and upgrade customization



## Product Model

Product Size	19.1"
Non-touch	TPC191-A200-3588A
Capacitive touch	TPC191-A210-3588A
Resistive touch	TPC191-A220-3588A

## Product Interface



## Product Specifications

## Screen Parameters


LCD size	19.1" TFT LCD
Resolution	1440*900 (16:10)
Viewing angle	80/80/80/80 (L/R/U/D)
Color	16.7M
Brightness	300 cd/m <sup>2</sup>
Contrast ratio	1000:1

## Touch Parameters

Touch type	10-point touch projection Capacitive touch screen	Single-point Resistance touch screen	Non-touch
Transmittance	≥88%	≥78%	≥92%
Input mode	Handwriting or Capacitance pen	Fingertip or stylus	/
Controller communication	USB	USB	/

## Hardware Configuration

CPU	RK3588 2.1 GHz, Quad-Core Cortex-A76 + Quad-Core Cortex-A55
Memory	8GB LPDDR4 (Optional 4GB/16GB/32GB, Supports up to 32GB)
Storage	64GB eMMC (Supports up to 256GB)
GPU	ARM Mali G610 MP4



## Physical Characteristics

Overall dimensions	W486x H332x D63mm
Size of opening	W469.6x H315.6mm

## Interface Parameters

Power interface	1*DC2.1, Supporting 12V-36V power input
Industrial terminals	1*12P Phoenix terminal (Power supply/RS232*1/RS485*1/CAN*1/GPIO*3)
USB	2*USB (1*USB2.0,1*OTG)
TF	1*TF card standard interface
HDMI	1*HDMI, Supporting HDMI data output, Up to 4K
SIM	1*SIM, Supporting various formats (Depending on 3G/4G module)
Network interface	2*LAN (1*100M, 1*1000M)
Audio interface	1*Audio I/O, Support audio input and output
COM	1*RS232
Reset key	Support (1*UBOOT)
WiFi antenna	1*WiFi antenna
Grounding post	1*Grounding post (GND)

## Product Reliability Parameters

Working temperature	-10°C~60°C
Storage temperature	-20°C~70°C
Relative humidity	Humidity: 95% Non-Condensing
Vibration protection	IEC 60068-2-64, Random, 5~500 Hz, 1 hr/axis
Impact protection	IEC 60068-2-27, Half sine wave, Lasting for 11ms
Product certification	CCC/CE/FCC/EMC/CB/ROHS
Waterproof grade	The front panel reaches IP65 protection level

## Power Parameters

Power input	DC 12V-36V
Static power	18W