

## ITX-YL82V1\_I522L



### Main Features

- Integrated Intel® I5 8260U 1.6GHz quad-core eight-thread processor
- 2x SODIMM 2400MHz DDR4, up to 64GB
- 2x RJ45 GbE ports
- 1x eDP, 2x HDMI1.4, 1x LVDS
- 2x M.2 slot, supports WiFi / 5G module
- 2x SATA3.0 ; 1x M.2
- 2x COM; 10x USB
- DC\_12V power supply

### Specification :

<b>Model No.</b>	ITX-YL82V1_I522L VER:1.0
<b>Processor</b>	Integrated 8th gen Intel® I5 8260U 1.6GHz quad-core eight-thread processor, TDP 15W Compatible with Intel® Whiskey Lake-U/Comet Lake-U/Coffee Lake-U 8th/10th Celeron /Pentium/I3/I5/I7 low-power processors
<b>Chipset</b>	SOC
<b>Memory</b>	2x SODIMM slot, supports 2400MHz DDR4 memory up to 64GB
<b>Display</b>	Integrated Intel® UHD Graphics, supports DirectX 12 OpenGL 4.5, supports 4K 2x HDMI1.4 interface, the highest resolution supported is: 4096x2304@24Hz 1x Support dual-channel 24bit LVDS interface 1x EDP interface, choose one of the two with LVDS through pop-up
<b>Network</b>	2x Intel I226 Gigabit network, supports network wake-up and PXE functions
<b>Storage</b>	2x SATA3.0 hard disk interface, transmission speed up to 6Gbps 1x M.2 slot, supports M.2 2260/2280 NVME PCIE x4/SATA adaptive standard SSD
<b>Audio</b>	Integrated ALC897 7.1+2-channel high-fidelity audio controller, supports MIC, Line_out, and power amplifier Support amplifier 4Ω 3W speaker
<b>Expansion slots</b>	1x M.2 slot, supports M.2 Key E 2230 WiFi module 1x M.2 slot, supports M.2 Key B 2242/4452 5G module (reserved, optional)
<b>Backplane I/O interface</b>	4x USB3.0 2x HDMI1.4 2x RJ45 Gigabit network interface (one network port is listed with USB2.0) 1x Line-out(green), 1x MIC(red) 1x DC12V power interface, supports 12V power input 1x SIM card slot (reserved, optional) 1x Clear CMOS button
<b>Built in I/O interface</b>	1x LVDS interface 2x 15pin, supports dual channel 24bit 1x LVDS backlight power supply interface 1x 6pin 1x EDP interface 2x 15pin, choose one of the two with LVDS through pop-up 2x RS232 serial interface, COM2 supports RS485/422 function 1x PS/2 keyboard and mouse interface (red) 1x 6Pin 4x USB2.0 interface 2x 5pin 2x USB3.0 interface 2x 10pin 1x Front audio interface 2x 5pin 1x Front panel switch button and indicator light interface 2x 5Pin 2x Hard drive power supply interface 1x 4pin 1x Power amplifier interface 1x 4pin 1x DC power interface 1x 4pin (can be used as 12V input power interface)
<b>Fan</b>	1x 4pin CPU fan interface; 1x 4pin system fan interface
<b>GPIO</b>	Supports four-in and four-out GPIO functions
<b>BIOS</b>	128Mb Flash ROM
<b>Watchdog</b>	Support hardware reset function (level 256, 0~255 seconds)
<b>OS</b>	Windows 10 /11/Linux
<b>Power supply</b>	DC 12V

<b>Working temperature</b>	-10°C ~ 60°C
<b>Storage temperature</b>	-20°C ~ 70°C
<b>Working Humidity</b>	5%-95% ( relative humidity, non-condensing)
<b>Dimension</b>	170mm x 170mm



## Ordering info:

NO.	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	485/422	Power
1	ITX-YL82V1_I522L VER:1.0	I5-8260U	1.6G	2*SODDR4	1	1	2ch/24Bit	1	2*I226V	10	2	COM2	DC12V