



深圳市千羽云创科技有限公司
Shenzhen Senba Innovation Technology Co., Ltd.

Factory Address: 8&13/F, Senhainuo Kechuang Building, Gongye road No.1, Hengchangrong High-tech Industrial Zone, Shilongzai Community, Baoan District, Shenzhen, 518108, China.




Contact Person: Aaron
Email: sales01@senbatech.com
Whatsapp: +86 159-1948-2214
Skype: +86 159-1948-2214
Website: www.senbatech.com

Catalogue of Network Appliance

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	STCW-N2600-4L	N2600	SOC	4x 1G LAN ports (82583V)	N/A	Single Channel NB/DDR3 Max: 4G	1x mSATA 1x SATA3.0	N/A	1x RJ45 Console	9" 1U Rackmount	Optional	Optional	 4LAN STCW-N2600-4L
	STCW-NET-D525	D525	SOC	4x 1G LAN ports (82574L)/ 6x 1G LAN ports (82574L)/ 6x 2.5G LAN ports (Intel I225V)	N/A	Single Channel NB/DDR3 Max: 8G	1x mSATA 1x SATA3.0	N/A	1x RJ45 Console	9" 1U Rackmount 2U Rackmount	Optional	Optional	 4LAN-6LAN STCW-NET-D525
	STCW-j1900-6L	J1900	SOC	6x 1G LAN ports (Intel I211AT)/ 6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR3 Max: 8G	1x mSATA 1x SATA3.0	Support 4G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-j1900-6L (
	R9FUZ V1.0(J1900)	J1900	SOC	4x 1G LAN ports (82583V)	N/A	Single Channel NB/DDR3 Max: 8G	1x mSATA 1x 2.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	N/A	N/A	 R9FUZ V1.0 (J1900) 4LAN Ra
	STCW-i3-3217U-6L	I3-3217U	SOC	6x 1G LAN ports (Intel I211AT)	N/A	Single Channel NB/DDR3 Max: 8G	1x mSATA 4x SATA3.0	Support 4G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-i3-3217U-
	STCW-J4125-4L	J4125	SOC	4x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 16G	1x mSATA 1x SATA3.0	Support 4G/5G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount	Optional	Optional	 (已压缩) 4LAN STCW-J4125-4L (
	R41EUZ V1.0(J4125)	J4125	SOC	4x 1G LAN ports (Intel I210)	N/A	Single Channel NB/DDR4 Max: 8G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R41EUZ V1.0 (J4125) 4LAN Ra

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	R41VUZ V1.0(J4125)	J4125	SOC	4x 2.5G LAN ports (Intel I225V)	N/A	Single Channel NB/DDR4 Max: 8G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	N/A	N/A	 R41VUZ V1.0(J4125) spec
	R41SLZ V1.0(J4125)	J4125	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 8G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R41SLZ V1.0(J4125) spec
	STCW-J4125-6L	N4000 J4125	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 32G	1x mSATA 2x SATA3.0	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-J4125-6L (
	STCW-JL-6L	N5105	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 32G	1x mSATA 2x SATA3.0	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-JL-6L (N4
	STCW-EHL-4L	J6412 (out of stock) J6413 (out of stock)	SOC	4x 2.5G LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 32G	1x mSATA 2x SATA3.0	Support 4G/5G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount	Optional	Optional	 (已压缩) 4LAN STCW-EHL-4L (J6
	STCW-EHLK-SFP-1U	J6412 J6413	SOC	6x 2.5G LAN ports (Intel I226V)	J6413 option 2x SFP+(1G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 1x SATA3.0 1x CF "One out of three"	Support 4G/5G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-EHLK-SFP-
	R641SLZ V1.0(J6412)	J6412	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 16G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/5G/WIFI&BT	1x RJ45 Console	1U Rackmount	N/A	N/A	 R641SLZ(J6412) Rackmount Appl
	STCW-ADLN-6L	N100 N305	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 48G	1x mSATA 1x SATA3.0 1x CF(option) "One out of three"	Support 4G/5G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-ADLN-6L (

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	STCW-NET-ADLN-4L	N100 N200 N305	SOC	4x 2.5G LAN ports (Intel I226V)	82599ES 2x SFP+ (10G) / 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Single Channel NB/DDR5 Max: 48G	1x mSATA 1x SATA3.0 1x CF "One out of three"	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 4LAN STCW-NET-ADLN
	STCW-TGL-6L	i3-1115G4 / i5-1135G7 / i7-1165G7	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 64G	1x M.2 NVME 1x mSATA 1x SATA	Support 4G/WIFI&BT	1x RJ45 Console	9" 1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-TGL-6L (i3)
	STCW-989NP-1U	i3-2350M i5-3320M i7-3520M	HM76	6x 1G LAN ports (82574L)/ 6x 2.5G LAN ports (Intel I226V)	82599ES 2x SFP+ (10G)/ 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Single Channel NB/DDR3 Max: 8G	1x mSATA 2x SATA3.0	N/A	1x RJ45 Console	1U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-989NP-1U
	STCW-NET-B75	i3-3240 i5-3470 i7-3770 E3-1230V2 E3-1245V2	B75 (LGA1155)	6x 1G LAN ports (i210/i211AT/82583V)	Intel_I350-AM2 2x SFP+(1G) Integrated	Dual Channel NB/DDR3 Max: 16G	1x mSATA 4x SATA3.0	N/A	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW--NET-B75
	STCW-NET-B85/Z87	i3-4170 i5-4570 i7-4770 E3-1230V3 E3-1245V3	B85 (LGA1150)	6x 1G LAN ports (i210/i211AT/82574L)	Intel_82599ES 2x SFP+(10G) Integrated	Dual Channel NB/DDR3 Max: 16G	1x mSATA 4x SATA3.0	Support WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW--NET-B85
	STCW-NET-B150	i3-6100 i5-6400 i7-6700 i5-7400 i7-7700	B150 (LGA1151)	8x 2.5G LAN ports (Intel I226V)	Intel_82599ES 2x SFP+ (10G)/ Intel_X710 4x SFP+ (10G)/ 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 3x SATA3.0	Support WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 8LAN STCW--NET-B150
	R320E-L8 V1.0(R270)	LGA1151 (6-9th gen CPU)	Q270/ Q250	8x 1G LAN ports (Intel I210)	2x SFP+ (1/10G) 4x SFP+ (1/10G) 2x Copper(1G) 4x Copper(1G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R320E-L8 V1.0(R270) Speci

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	R320E-L8 V1.0(R570)	LGA1200 (10/11th gen CPU)	H570	8x 1G LAN ports (Intel I210)	2x SFP+ (1/10G) 4x SFP+ (1/10G) 2x Copper(1G) 4x Copper(1G)	Dual Channel NB/DDR4 Max: 128G	1x mSATA 1x 2.5"/3.5" SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R320E-L8 V1.0(R570) Speci
	STCW-NET-C236	i3-6100 i5-7400 i7-8700 i5-9400 E3-1230V5	C236	8x 2.5G LAN ports (Intel I226V)	Intel_82599ES 2x SFP+ (10G) / Intel_X710 4x SFP+ (10G) / 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 4x SATA3.0	Support WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 8LAN STCW-NET-C236
	STCW-NET-C246	i3-8100 i5-8500 i5-9400 E-2124G E-2288G	C246	8x 2.5G LAN ports (Intel I226V)	(2x PCIe-X8 slots) 2x SFP+ (10G) 4x SFP+ (10G) 2x Copper(1G/2.5G) 4x Copper(1G/2.5G) "Combine freely"	Dual Channel NB/DDR4 Max: 64G	1x M.2 NVME 1x mSATA 4x SATA3.0	Support 4G/5G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 8LAN STCW-NET-C246
	STCW-NET-B660	i3-12100 i5-13400 i7-14700 Intel 12~14th Gen	B660	6x 2.5G LAN ports (Intel I226V)	Intel_82599ES 2x SFP+ (10G)/ Intel_X710 4x SFP+ (10G)/ 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Dual Channel NB/DDR4 Max: 64G	2x M.2 NVME 1x mSATA 4x SATA3.0	Support 4G/5G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW--NET-B660
	STCW-NET-C612	E5-2666V3 E5-2690V3 E5-2680V4 E5-2699V4 "dual CPU socket"	C612 support "IPMI"	2x 1G LAN ports (Intel I210AT)	(3x PCIe-X8 slots) 2x SFP+ (10G) 4x SFP+ (10G) 2x Copper(1G/2.5G) 4x Copper(1G/2.5G) "Combine freely"	8x Channel ECC DDR4 Max: 256G	2x M.2 NVME 1x mSATA 8x SATA	Support 4G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 3LAN STCW-NET-C612
	R320V-SF V1.0(R270)	LGA1151 (6-9th gen CPU)	Q250/ Q270	6x 2.5G LAN ports (Intel I226V)	2x SFP+ (1/10G) 4x SFP+ (1/10G) 2x Copper(1G) 4x Copper(1G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 1x 2.5"/3.5" SATA	Support 5G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R320V-SF V1.0(R270)specif
	R320V-SF V2.0(R590V)	LGA1200 (10/11th gen CPU)	Z590	6x 2.5G LAN ports (Intel I226V)	2x SFP+ (1/10G) 4x SFP+ (1/10G) 2x Copper(1G) 4x Copper(1G)	Dual Channel NB/DDR4 Max: 64G	1x mSATA 1x 2.5"/3.5" SATA	Support 5G/WIFI&BT	1x RJ45 Console	1U Rackmount	Optional	N/A	 R320V-SF V2.0(R590V)spec

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	STCW-B250	i3-6300 i5-6400 i7-8700 i9-9900	B250 (LGA1151)	6x 2.5G LAN ports (Intel I226V)	Intel_82599ES 2x SFP+ (10G)/ Intel_X710 4x SFP+ (10G) / 2x Copper(1G/2.5G)/ 4x Copper(1G/2.5G)	Dual Channel NB/DDR4 Max: 64G	2x mSATA 2x SATA3.0	Support 4G/5G/WIFI&BT	1x RJ45 Console	1U Rackmount 2U Rackmount	Optional	Optional	 (已压缩) 6LAN STCW-B250 (LGA
Firewall/Router Motherboards													
	ITX-VL305	N97	Alder Lake-N SOC	4x 1G LAN ports (WGI210AT)	N/A	Single Channel NB/DDR4 Max: 16G	1x SATA3.0 1x M.2 NVME	Support 4G/WIFI&BT	6x RS232/422/485	170mm x 170mm	N/A	N/A	 ITX-VL305 VER1.0(N97) spe
	ITX-M41V	J4125	Gemini Lake SOC	4x 2.5G LAN ports (Intel I225V)	N/A	Single Channel NB/DDR4 Max: 8G	2x SATA3.0 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	170mm x 170mm	Optional	N/A	 ITX-M41V VER1.1(J4125) sp
	ITX-M41E_B1	J4125	Gemini Lake SOC	4x 1G LAN ports (Intel I211)	N/A	Single Channel NB/DDR4 Max: 8G	2x SATA 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	170mm x 170mm	LAN1-2 supports BYPASS function	N/A	 ITX-M41E_B1 VER1.1(J4125) sp
	ITX-M9F	J1900	Bay trail SOC	4x 1G LAN ports (RTL82583V/82574L)	N/A	Single Channel NB/DDR3L Max: 8G	2x SATA 1x MSATA	Support 3G/4G/WIFI&BT	1x RJ45 Console	170mm x 170mm	Optional	N/A	 ITX-M9F VER1.5(J1900) 4L
	ITX-M9E	J1900	Bay trail SOC	4x 1G LAN ports (Intel I211)	N/A	Single Channel NB/DDR3L Max: 8G	2x SATA 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	170mm x 170mm	N/A	N/A	 ITX-M9E VER1.0 Specifications.pdf

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	D19SL	J1900	Bay trail SOC	6x 1G LAN ports (Intel I210AT)	N/A	Single Channel NB/DDR3L Max: 8G	2x SATA 1x MSATA	Support 3G/4G/WIFI&BT	1x RJ45 Console	180mm x 200mm	Optional	N/A	 D19SL VER1.0 Specification.pdf
	D41SL	J4125	Gemini Lake SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 8G	2x SATA3.0 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	180mm x 200mm	Optional	N/A	 D41SL VER1.0 Specifications.pd
	D41SL_B	J4125	Gemini Lake SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 8G	2x SATA3.0 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	180mm x 200mm	Support 2 sets of BYPASS functions	N/A	 D41SL_B VER1.0 Specifications.pd
	D641SL	J6412	Elkhart Lake SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR4 Max: 16G	1x SATA3.0 1x MSATA	Support 4G/5G/WIFI&BT	1x RJ45 Console	180mm x 200mm	Optional	N/A	 D641SL VER0.1 specification .pd
	Q570SL_6L	LGA1200 (10/11th gen CPU)	Q570	6x 1G LAN ports (WGI210AT) 1x LAN port (KTI226LM; support VPro)	N/A	4x Channel DDR4 Max: 128G	4x SATA3.0 3x M.2	Support 4G/WIFI&BT	1x RJ45 Console	220mm x 280mm	N/A	N/A	 Q570SL_6L VER1.1specificati
	K520E	5205U	Comet Lake SOC	6x 1G LAN ports (Intel I210AT)	N/A	Dual Channel NB/DDR4 Max: 64G	1x SATA3.0 1x MSATA	Support 5G/WIFI&BT	1x RJ45 Console	200mm x 193mm	N/A	N/A	 K520E VER 1.0 (5205U) Firewall
	K320V	I5-3210M	HM77	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR3 Max: 8G	1x SATA3.0 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	200mm x 193mm	N/A	N/A	 K320V VER 1.0 (i5-3210M) Firew

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	R67E	LGA1155	B75	6x 1G LAN ports (Intel I210AT)	N/A	Dual Channel NB/DDR3 Max: 32G	2x SATA 1x MSATA	Support 5G/WIFI&BT	1x RJ45 Console	245mm x 215mm	N/A	N/A	 R67E VER 1.0 (LGA1155) Firw
	R390V	LGA1151 (6-9th gen CPU)	Z390	6x 2.5G LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 64G	2x SATA3.0 1x MSATA	Support 5G/WIFI&BT	1x RJ45 Console	245mm x 215mm	N/A	N/A	 R390V VER 1.0(LGA1151) Fir
	R270E	LGA1151 (6-9th gen CPU)	Q250	6x 1G LAN ports (Intel I210AT)	N/A	Dual Channel NB/DDR4 Max: 64G	2x SATA3.0 1x MSATA	Support 5G/WIFI&BT	1x RJ45 Console	245mm x 215mm	N/A	N/A	 R270E VER 1.1(LGA1151) Fir
	H87SL	LGA1150	H87	8x 1G LAN ports (82574L)	N/A	Dual Channel NB/DDR3 Max: 16G	4x SATA3.0 1x MSATA	Support 3G	1x RJ45 Console	280mm x 209mm	Support 2 sets of BYPASS functions	N/A	 H87SL VER1.3 specification.pdf
	H17SL	LGA1151 (6-9th gen CPU)	H170	8x 1G LAN ports (I210AT/WGI211AT)	N/A	Dual Channel NB/DDR4 Max: 32G	1x SATA 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console	280mm x 209mm	N/A	N/A	 H17SL VER 1.0(LGA1151) Fir
	Z370SL-8L	LGA1151 (6-9th gen CPU)	Z370	8L-I210AT (1G) 1L-I219LM(support VPro)	N/A	4x Channel DDR4 Max: 128G	4x SATA3.0 3x M.2	Support 4G/5G/WIFI&BT	1x RJ45 Console	280mm x 220mm	N/A	N/A	 Z370SL_8L VER1.0 specificat
	Q570SL_8L	LGA1200 (10/11th gen CPU)	Q570	8x 1G LAN ports (WGI210AT) 1x LAN port (KTI226LM; support VPro)	N/A	4x Channel DDR4 Max: 128G	4x SATA3.0 3x M.2	Support 4G/5G/WIFI&BT	1x RJ45 Console	280mm x 220mm	N/A	N/A	 Q570SL_8L VER1.5 specificat

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
Multi-LAN Mini-pc													
	CW-X86-P5	N100/N200/i3-N305	SOC	2x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 32G	2x SATA3.0 1x M.2	Support WIFI&BT	6x USB2.0/3.0	112mm*100mm*36.3mm	N/A	N/A	 CW-X86-P5(N100) 2LAN Mini-PC
	CW-AD4L-N	N95/N100/N200/i3-N305	SOC	4x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 32G	1x SATA3.0 1x M.2 1x TF	Support WIFI&BT	8x USB2.0/3.0	178.3mm*135.6mm*55mm	N/A	N/A	 CW-AD4L-N(N100) 4LAN Mini-PC
	CW-ADLN-6L	N95/N100/N200/i3-N305	SOC	6x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 32G	1x SATA3.0 1x M.2 1x TF	Support WIFI&BT	5x USB2.0/3.0	178.3mm*125.2mm*55mm	N/A	N/A	 CW-ADLN-6L(N100) 6LAN Mini-PC
	ST-AD12N-8L	N97/N100/N200/i3-N305	SOC	8x 2.5G LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 32G	1x SATA3.0 1x M.2 1x TF	Support 4G/WIFI&BT	1xType-C 6x USB2.0/3.0	155mm*131.7mm*60mm	N/A	N/A	 ST-AD12N-8L(N100) 8LAN Mini-PC
	CW-AL-4L	N100/i3-N305	SOC	2x 2.5Gb LAN ports (Intel I226V)	2x 10Gb SFP+ ports (Intel 82599ES)	Single Channel NB/DDR5 Max: 32G	1x SATA3.0 1x M.2 1x TF	Support WIFI&BT	4x USB2.0 1x USB3.2 (Gen1) 1xType-C 3.2	126.5mm*158mm*60.2mm	N/A	N/A	 CW-AL-4L (N100) 2 LAN+2
	ST-AD12N-6S	N97/N100/N200/i3-N305	SOC	4x 2.5Gb LAN ports (Intel I226V)	2x 10Gb SFP+ ports (Intel 82599ES)	Single Channel NB/DDR5 Max: 32G	1x SATA3.0 1x M.2 1x TF	Support 4G/WIFI&BT	1xType-C 6x USB2.0/3.0	155mm*131.7mm*60mm	N/A	N/A	 ST-AD12N-6S(N100) 4 LAN+2 SF

Product Photos	Product Model	CPU (options)	Chipsets	Ethernet Port (options)	Expansion SFP+ Port (Fiber/Copper)	Memory	Storage	4G/5G/WIFI&BT	Other Ports	Dimension	BYPASS	Redundant (1+1) Power Supply	Specifications "Download"
	JF-304SI-S	N100	SOC	2x 1Gb LAN ports (RTL8111H)	N/A	Single Channel NB/DDR4 Max: 16G	1x SATA3.0 1x M.2	Support 4G/5G/WIFI&BT	2x DB9 RS232/485 1xType-C 5x USB3.0	156mm*127.5mm*52.5mm	N/A	N/A	 JF-304SI-S (N100) Fanless Ir
	W-N12	N100	SOC	4x 2.5Gb LAN ports (Intel I226V)	N/A	Single Channel NB/DDR5 Max: 16G	1x SATA3.0 1x M.2	Support WIFI&BT	2x DB9 RS232/485 6x USB2.0/3.0	152mm*126mm*52mm	N/A	N/A	 W-N12 (N100) industrial compu
	C2120Z-L4	N97	SOC	4x 1Gb LAN ports (Intel I210)	N/A	Single Channel NB/DDR4 Max: 16G	1x SATA 1x M.2	Support 4G/WIFI&BT	2x RS232/RS485 Phoenix connector 6x USB2.0/3.0	141.4mm*126mm*44mm	N/A	N/A	 C2120Z-L4 V2.0(N97) compi
	CW-J6-5L	J6412/J6413/J6426	SOC	5x 2.5Gb LAN ports (Intel I226V)	N/A	Dual Channel NB/DDR4 Max: 32G	2x SATA3.0 1x M.2	Support 4G/WIFI&BT	2x DB9 RS232 1xType-C 4x USB2.0/3.0	178.3mm*125.3mm*55mm	N/A	N/A	 CW-J6-5L (J6413 J6412) 5LAN+2C
	IBOX-B106	i3-6100U/i5-6200U/ Pentium 4415U	SOC	6x 1Gb LAN ports (Intel I211AT)	N/A	Single Channel NB/DDR4 Max: 16G	1x SATA 1x MSATA	Support 4G/WIFI&BT	1x RJ45 Console 4x USB3.0	215mm*110mm*53mm	N/A	N/A	 IBOX-B106 (i3-6100U; i5-620
Please click here to view more products on our website: www.senbatech.com													