


TPC080-M3010-ZS

The unit features a 2.5mm low-profile narrow-bezel panel design, specifically engineered for cabinet-mounted equipment. It comes standard with a 10-point capacitive touchscreen and supports VGA, HDMI, and DP display input interfaces. With an IP65-rated flush front panel and aluminum alloy die-cast housing, it delivers comprehensive isolation, heat dissipation, and robust protection, ensuring reliable support for industrial production.

Features

- Narrow-bezel panel, ideal for embedded cabinet mounting
- IP65 protection rating, supports wide-temperature & wide-voltage
- 2.5mm Ultra-Slim Narrow Bezel Panel, Designed for Cabinet Equipment
- Self-developed display driver board with multiple touch method options
- Industrial-grade protection, suitable for various harsh environments
- Supports VGA/HDMI/DP inputs with automatic signal channel identification



Model

Product Size	8"
Capacitive touch	TPC080-M3010-ZS

I/O Interface



Specification

Screen Parameter

Display type	8" TFT LCD screen
MAX.resolution	1024*768(4:3)
Viewing angle(H/V)	85/85/85/85 (L/R/U/D)
Luminance (cd/m²)	250~300 cd/m²
Contrast ratio	800:1

Touch Parameter

Touchscreen	Projection capacitive touch 10-point multi touch
Light transmission	≥88%
Controller	USB (COM customized)


Power Parameter

Power input	DC 12V-36V
Power adapter	24V/1.5A

Hardware Configuration

CPU	RTD2513BR	System language	Multilingual (default: English)
Key function	AUTO/MENU/POWER/LEFT/RIGHT	Video input	PC-RGB:Format Up to 1920*1080@60Hz Color 16bit/24bit/32bit

Dimension



Physical Characteristic

Overall dimensions	W226.6x H167.6x D44.5mm
Installation size	W223.53 x H164.53mm
Material	Aluminum alloy
Color	Black, optional silve
Installation	Support Embedded installation with iron sheet/ Back-mounted Installation, etc.

Interface Parameter

PowerSW	1*PowerSW
Power interface	1*12P Phoenix terminal (optional threaded DC 5.52.1mm connector)
HDMI	1*HDMI, Support HDMI data input, With a maximum of 1080P
Touch interface	1*TOUCH (USB protocol) with RJ45-to-USB touch cable (std.)
VGA	1*VGA
DP	1*DP
Audio interface	1*Audio I/O, Support audio input and output
Grounding	1*GND

Reliability Parameter

Operating temperature	-10°C~60°C (-20°C~70°C can be customized)
Storage temperature	-20°C~70°C
Relative humidity	95% non-condensing